

规格承认书

APPROVAL SHEET

产品名称 Product Name	美式電話轉接頭 American splitter to two American plugs
型号 Model	2197

出厂签章（EX FACTORY APPROVALS）				
核准 APPROVED BY	审核 CHECKED BY	品管部 Q.A.	工程技术部 ENGINEERIG	
黄敏祥	黄勋	车福琴	车叶飞	
客户确认（customer confirmation）				
	核准 APPROVED BY	审核 CHECKED BY	品管部 Q.A.	工程技术部 ENGINEERIG
接受 accept				
驳回 reject				
	说明(Description):			

日期(Date): 2015-06-12

ITEM	NO	DESCRIPTION	MOLD No.	QTY	Part No.	Part No. m/s	Case	Signature	Checked
01	CK 20006-01	KU-2 SHELL, ABS, 6P4C PLUG & 6P4C JACK		1 SET					
02	CK 20000-A7	62 S, 6C, IVORY	DZ-QT-012	2 PCS					
03	PP 01207093-BRBP	JUMP WIRE, BROWN, OD: 0.93mm, PVC		90 mm					
04	PP 01207093-GRBP	JUMP WIRE, GREEN, OD: 0.93mm, PVC		90 mm					
05	PP 01207093-YEBP	JUMP WIRE, YELLOW, OD: 0.93mm, PVC		90 mm					
06	PP 01207093-WHBP	JUMP WIRE, WHITE, OD: 0.93mm, PVC		90 mm					
07	CP 930008-2	PE BAG, 8" x 10CM		1 PC					
08	CP 930020-1	LABEL, "FLEXICON", 60" x 22mm		1 PC					

PACKING

CONNECTIONS:

MODULAR PLUG	US 6x4 JACK	US 6x4 JACK
2(WHITE)	2	2
3(BROWN)	3	3
4(GREEN)	4	4
5(YELLOW)	5	5

一般公差				技术要求The technical requirements 1 表面应平整光洁，无毛刺 1.surface should be smooth, without burr 2 未注尺寸公差按一般公差中级 2 Did not note size tolerance according to general tolerance
标示尺度	精级	中级	初级	
0.5—3	±0.05	±0.10	±0.15	
3—6	±0.05	±0.10	±0.20	
6—30	±0.10	±0.10	□0.50	
3—120	±0.15	±0.20	±0.80	
120—315	±0.2	±0.50	±1.20	
315—1000	±0.03	±0.80	±2.00	

				美式電話轉接頭 American splitter to two American plugs			外形图 Outline drawing
设计 design		标准化 standard		图样标记 marker	数量 number	比例 ratio	RBS-2197
校对 proofread		审定 judgement				1: 1	
审核 audit							
工艺 process		日期 date		第一页 共一页			

型号 Item No.	RBS-2197	产品名称 Description	美式電話轉接頭 American splitter to two American plugs
1. 额定值(rated value) 1.1 额定电压(The rated voltage) 30V 1.2 额定电流(Rated current)20mA 2 使用环境条件conditions 2.1 环境温度(temperature)：-25——+40℃ 2.2 相对湿度(humidity)：≤93 % 3 结构尺寸：（见图纸） 4 技术特性 Technical characteristics 4.1 环境测试条件(test conditions): 5℃—35℃，湿度(humidity) 65-90%，标准大气压下。(Under normal atmospheric pressure.) 4.2 物理性能(Physical) 4.21 接触线：锡镀黄铜，镀金，插头可重复插拔不小于 600 次。 Contact wire: tin plated brass, gold plated the plug can be inserted is not less than 600 times 4.24 塑料件采用ABS注塑而成，性能满足国际标准。 Plastic made BY ABS material, performance to meet international standards. 4.25 标识：标识完善、清晰 Marks: perfect and clear 4.3 电气性能 Electrical properties			

	项目 item	条件 Conditions	要求 requirements
	绝缘电阻 Insulation resistance	相互绝缘的接线之间，施加电压为 DC500±50V 作用时间 1 分钟 Applying 500 DC voltage between each other ,Last 1 minute	标准大气压下 ≥1000 兆欧 Under normal atmospheric pressure,More than 1000 megohm
	耐压 Withstand voltage	两相邻触点间能承受 AC250±50V 电压，作用时间为 1 分钟 Between two adjacent contacts to withstand 250 AC voltage, last time is 1 minutes	无击穿或飞弧 No breakdown or flashover
	插入力 Insertion force	标准大气压下 Under normal atmospheric pressure	插头和插孔之间承受压力强度，9.8N the Stress between plug and socket is no more than 9.8 N
	振动试验 Vibration test	标准大气压下 Under normal atmospheric pressure	频率范围： 10HZ-55HZ frequency range 10HZ-55HZ 速度幅值： 5m/s Velocity amplitude 5m/s 循环数： 20 Cycle count: 20

5: Packing

普通中性包装

Ordinary neutral packing