

Fiber Optic Patch Cord

SC/UPC-SC/UPC/OM3-DX

This fiber optic patch cord is a fiber optic cable assembled SC UPC connectors at both ends that allow it to be rapidly and conveniently connected to one equipment to the other one. It is used to attach one device to another for signal routing.



Features:

- Low insertion loss
- High return loss
- Excellent mechanical endurance
- Good in repeatability and exchangeability

Connector type: SC

Polish type: UPC

Cable: MM OM3, Duplex, PVC

Cable diameter: Ø 3.0mm or Ø 2.0mm

Length: 1m, 2m, 3m ... other request

Color: aqua

	P/N	Description
1	92434401	Opt P/C MM Duplex Aqua 0.5m SC-D/SC-D OM3
2	92434402	Opt P/C MM Duplex Aqua 1m SC-D/SC-D OM3
3	92434403	Opt P/C MM Duplex Aqua 1.5m SC-D/SC-D OM3
4	92434404	Opt P/C MM Duplex Aqua 2m SC-D/SC-D OM3
5	92434405	Opt P/C MM Duplex Aqua 3m SC-D/SC-D OM3
6	92434406	Opt P/C MM Duplex Aqua 5m SC-D/SC-D OM3
7	92434407	Opt P/C MM Duplex Aqua 10m SC-D/SC-D OM3



Parameter:

Parameter	Unit	Standard & Requirement
Insertion Loss (Typical)	dB	≤ 0.3
Return Loss	dB	≥ 30
Exchangeability	dB	≤ 0.2
Durability	Time	> 1000
Vibration	dB	≤ 0.2
Operating Temperature	°C	- 40 ~ + 75
Storage Temperature	°C	- 45 ~ + 85

Application:

- ◆ Telecommunications
- ◆ FTTX
- ◆ CATV
- ◆ Optical communication system