942100 AB002 Chip Key Chain

Material: ABS
Frequency:125KHZ
Dimensions:52.5x35.2x9mm
Color: blue,black,gray,yellow,red

942104 - 350U-Bracket - 0.32Kg, 180X28X43mm - No frame glass

Material: Sandblasting surface of high strength aluminum alloy
Shell: Aluminum anodic oxidation
Applicable door type: no frame glass door
Weight: 0.18kg
Size:180x28x40mm

942105 - 350 ZL-Bracket set, 0.7kg

Material: Sandblasting surface of high strength aluminum alloy
Shell: Aluminum anodic oxidation
Applicable door type: Inward opened wooden door, metal door and narrow frame door
Weight:0.7kg
L Bracket Size:250x50x30mm
Z Bracket Size:180x50x45mm

942116 280 U-Brakect set,0.18kg,180X28X43mmNo frame glass

Material: Sandblasting surface of high strength aluminum alloy
Shell: Aluminum anodic oxidation
Applicable door type: no frame glass door
Weight: 0.18kg
Size:180x28x40mm

942117 280 ZL-Bracket set, 0.68kg

Material: Sandblasting surface of high strength aluminum alloy
Shell: Aluminum anodic oxidation
Applicable door type: Inward opened wooden door, metal door and narrow frame door
Weight:0.68kg
L Bracket Size:249x30x50mm
Z Bracket Size:180x50x45mm

942115 - Emergency Resettable Break Glass(Green, Plastic Breaker)

Size:86Lx86Wx50H(mm)

Materials:Fireproof Material, Sandblast Finished.

Voltage:3A 36VDC Max

Output:NO\NC\COM

Operating temp:-10℃ ~ 55°C (14°F-131°F)

Operating Humidity:0-95% (non- condensing)